

PRODUCT INFORMATION

ANTICHLOR

Antichlor is used in the dyeing process where chlorine levels of the incoming water will cause variations in shade. It can be used to either treat water in a large holding tank or in each dye batch or bleach bath.

SPECIFICATIONS:

Appearance:	Clear Liquid
pH:	10 ± 0.5
Specific Gravity:	1.20 ± .02

APPLICATIONS:

Use 1/4% OWF. Fill dye tub with water and Antichlor. Circulate water for five minutes to give the product time to kill the chlorine. Add the fabric and continue as normal. If treating the water prior to adding the cloth is not possible, treating the fabric will not harm dyeing.

Antichlor should be used in the same way in a bleach bath where peroxide is used because chlorine kills peroxide.

The data and suggested formulations in this bulletin are based on information believed to be reliable and are offered solely for evaluation, investigation and verification of the numerous factors affecting results. Paradigm Lab's products are sold with the understanding the purchasers will make their own tests to determine the suitability of these products for the particular use. We assume no liability or responsibility for any damage to person or property resulting from or incident to the use of our products.

Statements concerning the use of Paradigm Lab's products are not be construed as recommending the infringement of any patent, and no liability for infringement arising out of any such use is assumed.



PARADIGM LABS, Inc.

P.O. BOX 138, PINE GROVE, PA 17963-0138
(570) 345-2600 – FAX (570) 345-2800