

# PRODUCT INFORMATION

## SOILRESIST LT-100F

SOILRESIST LT-100F is a water-based fluorochemical used to repel water and oil on woven fabrics. When used as a finishing agent, it provides excellent soil resistance on a wide variety of fibers. SOILRESIST LT-100F is designed to prevent both wet and dry soiling, and to impart oil and water repellency. SOILRESIST LT-100F can be used on most types of synthetic and natural fibers and their blends. SOILRESIST LT-100F can be applied by spraying or dipping.

### SPECIFICATIONS:

Appearance:	Off white, milky emulsion
Specific Gravity:	1.05
pH:	5.0 ± 0.5
Solids:	17% +/- 0.5

### CHARACTERISTICS:

SOILRESIST LT-100F cures at a low temperature to develop water, oil, and soil resistant properties. It is designed to be applied as a foam through a parabolic unit or other foaming equipment.

Improves abrasion resistance with higher pick-up weights.

SOILRESIST LT-100F dilutes readily in water and mixes with Raycoflame FRA<sup>1</sup> allowing application of two products in one step.

SOILRESIST LT-100F is non-flammable.

<sup>1</sup>Raycoflame FRA is a flame-retardant product for use on both man-made and natural fibers and is compatible with SOILRESIST LT-100F. For more information contact your Paradigm Labs representative.

The data and suggested formulations in this bulletin are based on information believed to be reliable and are offered solely for evaluation, investigation and verification of the numerous factors affecting results. Paradigm Lab's products are sold with the understanding the purchasers will make their own tests to determine the suitability of these products for the particular use. We assume no liability or responsibility for any damage to person or property resulting from or incident to the use of our products.

Statements concerning the use of Paradigm Lab's products are not to be construed as recommending the infringement of any patent, and no liability for infringement arising out of any such use is assumed.



**PARADIGM LABS, Inc.**

P.O. BOX 138, PINE GROVE, PA 17963-0138  
(570) 345-2600 – FAX (570) 345-2800